(19) World Intellectual Property Organization

International Bureau





(43) International Publication Date 14 July 2005 (14.07.2005)

PCT

(10) International Publication Number WO 2005/064116 A1

(51) International Patent Classification⁷: G01F 1/688, 1/684, 1/74

E21B 47/10,

Alexander, Michael [NL/NL]; Sleedoornlaan 23 NL-3053 ZN Rotterdam (NL).

(21) International Application Number:

PCT/EP2004/053672

(22) International Filing Date:

22 December 2004 (22.12.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

03104971.1

24 December 2003 (24.12.2003) EP

- (71) Applicant (for all designated States except CA, SM, US): SHELL INTERNATIONALE RESEARCH MAATSCHAPPIJ B.V. [NL/NL]; Carel van Bylandtlaan 30, NL-2596 HR The Hague (NL).
- (71) Applicant (for CA only): SHELL CANADA LIMITED [CA/CA]; 400 4th Avenue S.W., Calgary, Alberta T2P 2H5 (CA).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): VAN DER SPEK,

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

ZW.

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: DOWNHOLE FLOW MEASUREMENT IN A WELL

(57) Abstract: A method for downhole flow measurement comprises installing a fibre optical distributed temperature sensor (DTS) system along at least part of the length of an inflow region of the well and using the sensor to measure fluctuations of the temperature of fluids flowing from the formation into the well and the velocity at which said natural fluctuations migrate in downstream direction through the well. The measured temperature variations may be low frequency temperature fluctuations of between 0.1 and 0.5 Degrees Celsius, which gradually die out downstream of the inflow region(s) of the well.

